


TECHNICAL REGULATIONS JAPAN 20+ , 2021

| NO. | CONTENTS | SINGLE CAM | TWIN CAM | |
|-----|---|---|--|---------------|
| | | | UNDER 2000 CC. | OVER 2000 CC. |
| 1 | Race cars must be over 20 years old (from the current year). | O | O | O |
| 2 | Car's weight include that of driver | 900 kg. | 1,000 kg. | 1,075 kg. |
| 3 | Weight for car must be in block shape with lid and it must be fixed firmly with car's body by using bolts and nuts beside of driver's seat | O | O | O |
| 4 | Engine position and its holding point or mounting point must be remained as factory standard. | O | O | O |
| 5 | Car's shape must be remained as can tell by looking which brand and model it is. | O | O | O |
| 6 | Any kind of air compression is not allowed to installed. | O | O | O |
| 7 | Any gas or liquid substance that means to mix with air in airintake tube as to increase the efficiency of engine combustion is not allowed. | O | O | O |
| 8 | DRY SUMP System | X | X | X |
| 9 | Transmission | Manual "H" PATTERN | Manual "H" PATTERN SEQUENTIAL + 40 kg. | |
| 10 | TRACTION CONTROL | X | X | X |
| 11 | Suspension's holding points must be remained as factory standard. | O | O | O |
| 12 | Shock absorber position and its working system must be remained the same as factory setting | O | O | O |
| 13 | Suspension system parts must be remained standard as factory setting, | O | O | O |
| 14 | Aero part can be freely installed as it is not harmful to other | O | O | O |
| 15 | Tail pipe must point out at the back of the car only. | O | O | O |
| 16 | Tyres that allowed to used in the race (Provided from organizer only) |  | HANKOOK Z221 195/55-15 5,100.00 baht | |
| 17 | Rain tires, do not use WET HANKOOK Z207 tires, use HANKOOK radial tires, HANKOOK RS4 tires and HANKOOK Z221 tires only. | O | O | O |
| 18 | Safety system (Roll,Racing Seat, at least 5 anchors BELT,Electric Breaker,Fire Extinguisher) and window net at driver side. | O | O | O |