



NO.	CONTENTS	SUPER TURBO		D1	
		2 WD	4 WD	2 WD	4 WD
1	Year of the car is open			✓	
2	Car's weight include that of driver	1,350 kg.	1,400 kg.	1,250 kg.	1,300 kg.
3	Weight for car must be in block shape with lid and it must be fixed firmly with car's body by using bolts and nuts beside of driver's seat			✓	
4	Car's body and engine do not have to be that of the same brand.			✓	
5	Car's shape must be remained as can tell by looking which brand and model it is			✓	
6	Cockpit floor must be that of standard. Cutting off is not allowed.			✓	
7	Engine	Not Over 3250 cc. Turbo installed		Not Over 2250 cc. Turbo installed	
		3 rotor Turbo installed		2 rotor Turbo installed	
8	The car is allowed to install only 1 turbo with air restrictor. The narrowest part must not exceed 10 cm. measured from the the tip of compressor wheel. (ROTARY engine)	43 mm.		38 mm.	
		47 mm.		42 mm.	
9	The material of engine block and cylinder head cover must be as factory standard. Holding points must be remained in both benzine and diesel engine.			✓	
10	DRY SUMP system			✓	
11	Any gas or liquid substance that means to mix with air in air intake tube as to reduce temperature is not allowed. Only Intercooler Air-To-Air type is allowed			✓	
12	Water Inter Cooler is allowed but water pump and any other external spray as to reduce the heat of inter cooler is not allowed			✓	
13	Transmission	Manual Transmission			
		Automatic			
		Paddle Shift			
		Sequential Paddle Shift			
14	Suspension's holding point can be moved from the original point not more than 20 mm. in radius.			✓	
15	Shock absorber position and its working system must be remained the same as factory setting			✓	
16	Suspension system parts must be remained standard as factory setting,			✗	
17	Aero part can be freely installed as it is not harmful to other			✓	
18	Tail pipe must point out at the back of the car only.			✗	
19	Fuel tank are free. If installed in the cabin, it must be completely surrounded by a fireproof and shockproof structure.			✓	
20	Allowed to add no more than 5 liters to tank A.			✓	
21	Tyres that allowed to used in the race (Provided from organizer only)			245/625-17 225/635-18 260/650-18	
22	Rain tires must use radial HANKOOK brand tires only, and do not use WET HANKOOK Z207 tires.			✓	
23	Rear camera must be installed and there must be at least 5" monitor installed inside cockpit in middle console.			✓	
24	Must install Apps STT RACE CONTROL			✓	
25	Safety system (Roll,Racing Seat, at least 5 anchors BELT,Electric Breaker,Fire Extinguisher) and window net at driver side.			✓	