



NO.	CONTENTS	D5
1	Year of the car is open.	✓
2	Car's weight include that of driver.	<p style="text-align: center;">NA. Engine Single Cam</p> <p style="text-align: center;">Not more than 1200 cc. = 980 kg. 1201 cc. - 1250 cc. = 995 kg. Not more than 1350 cc. = 1,010 kg.</p> <p style="text-align: center;">NA. Engine Twin Cam</p> <p style="text-align: center;">Not more than 1350 cc. = 1,040 kg. **Engine K12m = 995 kg.</p> <p style="text-align: center;">TURBO Engine</p> <p style="text-align: center;">Not more than 1000 cc. = 1,040 kg. *** Grade Racers PRO + 25 kg. *** Grade Racers AM + 15 kg.</p>
3	Weight for car must be in block shape with lid and it must be fixed firmly with car's body by using bolts and nuts beside of driver's seat.	✓
4	Car's body and engine do not have to be that of the same brand.	✓
5	Car's shape must be remained as can tell by looking which brand and model it is.	✓
6	Cockpit floor must be that of standard. Cutting off is not allowed.	✓
7	Engine	<p style="text-align: center;">Not more than 1350 cc. N/A 1000 cc. Turbo Installed</p>
8	For N/A engine, there must be only 1 working throttle. The narrowest part must not exceed 10 cm. measured from the tip of compressor wheel.	49 mm.
9	Front and rear turbos are the original ones that were installed on that model car. Do not modify them.	✓
10	Internal engine is free to modify.	✓
11	The material used for engine block and cylinder head must be remained as factory setting. And must use maintain its original location point.	✓
12	The original intake manifold must not be modified. If adjusted + 25 kg., air filter are free.	✓
13	Can use the modify intake manifold. Plus 25 kg. extra weight.	✓
14	DRY SUMP system.	✗
15	Independent ECU box.	✓
16	Independent body wiring and engine wiring.	✓
17	Any gas or liquid substance that means to mix with air in air intake tube as to reduce temperature is not allowed. Only intercooler Air-To-Air type is allowed.	✓
18	Transmission	<p style="text-align: center;">Manual Transmission</p> <p style="text-align: center;">Sequential + Gear lever + 20 kg.</p> <p style="text-align: center;">Sequential + Paddle Shift +30 kg.</p>
19	Suspension holding point must be remained as it comes with the model.	✓
20	Material of rubber mounting can be altered but not Ball Joint.	✓
21	Shock absorber position and its working system must be remained the same as factory setting.	✓
22	Aero part can be freely installed as it is not harmful to other.	✓
23	Tail pipe must point out at the back of the car only.	✓
24	Fuel tank are free. If installed in the cabin, it must be completely surrounded by a fireproof and shockproof structure.	✓
25	Allowed to add no more than 5 liters to tank A.	✓
26	Tyres that allowed to used in the race (Provided from organizer only).	  <p style="text-align: right;">195/50-15</p>
27	Rear camera must be installed and there must be at least 5" monitor installed inside cockpit in middle console.	✓
28	Must install Apps STT RACE CONTROL.	✓
29	Safety system (Roll bar, Racing seat, at least 8 anchors BELT, Electric breaker, Fire extinguisher) and window net at driver side.	✓