

## **TECHNICAL REGULATIONS**

## **SUPER NZ** 2025



	SULEK NZ 2025	CHOMANO
NO.	CONTENTS	SUPER NZ
1	Year of the car is open.	<b>√</b>
2	Car's weight include that of driver.	1,100 kg.
3	Weight for car must be in block shape with lid and it must be fixed firmly with car's body by using bolts and nuts beside	✓
	of driver's seat.	
4	Body and engine must be of the same brand.	<b>V</b>
5	Car's shape must be remained as can tell by looking which brand and model it is.	V
6	Cockpit floor must be that of standard. Cutting off is not allowed.	<b>V</b>
7	Engine	Engine model NZ  Not More Than 1550 cc.  N/A  Compression ratio not more than 10.5:1
8	It must be the original butterfly valve that actually works. Size not exceeding 45 mm., measured at the narrowest point of the hou	<b>✓</b>
9	Internal engine is free to modify.	<b>✓</b>
10	The material used for engine block and cylinder head must be remained as factory setting. And must use maintain its original	<b>✓</b>
	location point.	,
11	The original intake manifold must not be modified. If adjusted + 25 kg., air filter are free.	<b>V</b>
12	Can use the modify intake manifold. Plus 25 kg. extra weight.	<b>√</b>
13	DRY SUMP system.	X
14	Independent ECU box.	✓
15	Independent body wiring and engine wiring.	<b>√</b>
16	Any gas or liquid substance that means to mix with air in air intake tube as to reduce temperature is not allowed.	<b>√</b>
17	The tranmission system must be the original Syncromet system only, the gear ratio can be changed.	Manual Transmission only
18	Suspension holding point must be remained as it comes with the model.	<b>√</b>
19	Material of rubber mounting can be altered but not Ball Joint.	<b>√</b>
20	Shock absorber position and its working system must be remained the same as factory setting.	✓
21	Aero part can be freely installed as it is not harmful to other.	<b>√</b>
22	Tail pipe must point out at the back of the car only.	<b>√</b>
23	Fuel tank are free. If installed in the cabin, it must be completely surrounded by a fireproof and shockproof structure.	<b>√</b>
24	Allowed to add no more than 5 liters to tank A.	<b>✓</b>
25	Tyres that allowed to used in the race (Provided from organizer only).	195/50-15
26	Rear camera must be installed and there must be at least 5" monitor installed inside cockpit in middle console.	<b>✓</b>
27	Must install Apps STT RACE CONTROL.	<b>√</b>
28	Safety system (Roll bar, Racing seat, at least 8 anchors BELT, Electric breaker, Fire extinguisher) and window net at driver side.	<b>✓</b>



